



Active Lubricants

TURBO - 3

Mono-grade Diesel Engine Oil

Technical Data Sheet

TURBO-3 is a heavy duty crank case oil to give good diesel performance at the CF – 4 levels. It provides good detergency, oxidation, corrosion, resistance, wear & foam control. It has an added advantage of higher TBN value than other API CF – 4 lubricants for longer drain period and better corrosion protection.

TURBO-3 is recommended for taxi-cabs, fleet cars, buses, on the road trucks, delivery vehicles and construction equipment.

TURBO-3 meets API service CF – 4 classifications.

It provides the following consumer benefits:

- Protect against rust & corrosion.
- Good protection against wear under mild service condition.
- Improves fuel economy.
- Reliable Performance

The typical characteristics of TURBO-3 are:

TEST METHODS	SAE VISCOSITY GRADE	50
D 445	Kinematic Viscosity @ 40°C, cSt	220
D 445	Kinematic Viscosity @ 100°C, cSt	19.5
D 4052	Density @ 15°C, kg/m ³	0.9
D 2270	Viscosity Index	101
D 97	Pour Point, °C	-9
D 93	Flash Point, °C	247
D 2896	TBN, mg KOH/g	8.5

Product specifications are based on average values. They are not limiting values and are subject to change due to ongoing research and development. Some variation, not effecting performance can be expected

Active Lubricants

Production : TURKEY | U.A.E.

United Arab Emirates

info@activelubricants.com

www.activelubricants.com

