



Active Lubricants

VOLT - 1

GASOLINE ENGINE OIL

Technical Data Sheet

VOLT-1 is blended from high quality mineral base stocks with advance additive package that gives good detergency and dispersing properties. It is designed for older gasoline engines operating under mild service conditions. This oil provides good control over engine wear and deposit and protects against rust and corrosion.

VOLT-1 is available in SAE 20W-50. It meets API service SL/CF classification. US military specification MIL-L-2104B. This oil can be used where SB and CB grades are specified.

VOLT-1 provides the following consumer benefits:

- Reliable performance.
- Keep engine clean.
- Protect against rust and corrosion.
- Control over low temperature slugging

The typical characteristics of VOLT- 1 are:

TEST METHODS	SAE VISCOSITY GRADE	20W-50
D 445	Kinematic Viscosity @ 40°C, cSt	170
D 445	Kinematic Viscosity @ 100°C, cSt	15.8
D 4052	Density @ 15°C, kg/m ³	0.902
D 2270	Viscosity Index	95
D 97	Pour Point, °C	-9
D 93	Flash Point, °C	227
D 2896	TBN, mg KOH/g	5

Product specifications are based on average values. They are not limiting values and are subject to change due to ongoing research and development. Some variation, not effecting performance can be expected

Active Lubricants

Production : TURKEY | U.A.E.

United Arab Emirates

info@activelubricants.com

www.activelubricants.com

