



Active Lubricants

VOLT - 3

Premium Multi-grade Motor Oil

Technical Data Sheet

VOLT-3 is multi grade motor engine oil, which provides outstanding performance in all passenger cars, light trucks and high performance gasoline engines. This oil is blended from top quality HVI Base Stocks and advance additive package containing detergent, dispersant, anti-rust, anti-oxidation, anti-wear and anti-foaming properties.

VOLT-3 is designed specially to cater to the severest of requirements of high performance gasoline and diesel engines. It gives the right level of detergency and dispersancy to keep the engine free of deposits and protect against wear and corrosion. It gives long engine life, provides improved fuel efficiency, starting at low temperature, as well as providing excellent lubrication all year round, in hot and cold weather.

VOLT-3 meets API service SM classification.

It provides the following consumer benefits:

- Excellent wear and deposits control.
- Prevents piston ring sticking.
- Reduce maintenance cost and eliminates season oil changes.
- High oxidation resistance.
- Catalyst proven.
- Superior viscosity intention.

The typical characteristics of VOLT- 3 are:

TEST METHODS	SAE VISCOSITY GRADE	5W-30
D 445	Kinematic Viscosity @ 40°C, cSt	104
D 445	Kinematic Viscosity @ 100°C, cSt	14.01
D 4052	Density @ 15°C, kg/m ³	0.896
D 2270	Viscosity Index	137
D 2896	TBN, mg KOH/g	7.1
X-ray	Phosphorus, m%	0.03
D 97	Pour Point, °C	-18
D 93	Flash Point, °C	217

Product specifications are based on average values. They are not limiting values and are subject to change due to ongoing research and development. Some variation, not effecting performance can be expected

Active Lubricants

Production : TURKEY | U.A.E.

United Arab Emirates

info@activelubricants.com

www.activelubricants.com

